

Features

- RoHS compliant
- Efficiency up to 77%
- 6kVDC Isolation
- Single output
- Internal SMD Construction
- Continuous short circuit Protection
- Wide temperature performance at full 1 Watt load, -40°C to 85°C



Model Selection Guide

Order Code	Vin(V)		Output		Max capacitive Load	Efficiency(%) (Typ)
	Nominal	Range	Vo(V)	Io(mA)		
H0505S-1W	5	4.5-5.5	5	200	220	71
H0509S-1W			9	111	150	72
H0512S-1W			12	83	100	73
H0515S-1W			15	67	100	74
H1205S-1W	12	10.8-13.2	5	200	220	71
H1209S-1W			9	111	150	72
H1212S-1W			12	83	100	73
H1215S-1W			15	67	100	73
H1224S-1W			24	42	68	75
H2405S-1W	24	21.6-26.4	5	200	220	72
H2409S-1W			9	111	150	73
H2412S-1W			12	83	100	73
H2415S-1W			15	67	100	75
H2424S-1W			24	42	68	77

*All the specifications typical at Ta=+25°C resistive load, nominal input voltage and rated output current unless otherwise noted.

Input Characteristics

Parameter	Condition	Min	Typ	Max	Units
Input Surge Voltage (1 sec. Max.)	3.3V Input Models	-0.7	--	6	VDC
	5V Input Models	-0.7	--	9	
	12V Input Models	-0.7	--	18	
	24V Input Models	-0.7	--	30	
Input Filter	All Models	Internal Capacitor			


Output Characteristics

Parameter	Condition	Min	Typ	Max	Units
Line regulation	Vin change 1%	±1.2	--	±1.5	%
Switching frequency	Full load, nominal input	--	100	--	KHz
Load regulation	10%~100% load	6.5	--	15	%
Ripple and noise	BW=DC to 20MHz	--	75	≤100	mVp-p
Short circuit Protection		Continuous, Automatic Recovery			


General Characteristics

Parameter	Condition	Min	Typ	Max	Units
Operating Temperature	All output types	-40	--	+85	°C
Storage		-55	--	+125	°C
Storage humidity		--	--	+95	%
Cooling	Free air convection	--	--	--	
Isolation voltage	1mA≤1minute	--	6000	--	VDC
Isolation resistance	500VDC	1000	--	--	MΩ
Switching Frequency		--	100	--	KHz
MTBF	3.5×10 ⁶				K hours

Tolerance Envelopes Curve




Temperature Derating Graph Curve



Input/Output Ripple Reduction

Reduce output ripple, it is recommended to use capacitors at the input/output.




External Capacitor Table

Parameter	5	12	15	24	
Vin(VDC)	5	12	15	24	
Cin(μF)	4.7	2.2	2.2	1	
Vout(VDC)	5	9	12	15	24
Cout(μF)	10	4.7	2.2	1	0.47

Note

1. To ensure this module can operate efficiently and reliably, During operation, the minimum output load is not less than 10% of the full load.
2. Other input and output voltage may be available, please
3. Specifications subject to change without notice

Mechanical Dimension & Pin Connections



Note:
Unit:mm(inch)

Pin	1	2	5	7
Function	Vin	GND	-Vo	+Vo